

ATX720

COMPACT ARTICULATED LOADER



TELESCOPIC BOOM. The telescopic boom on the ATX720 extends 29.1 in (73.9 cm) for loading materials to a dump height of 114 in (290 cm) in hinge pin height. The telescopic boom can also aid in dumping material over the back of a retaining wall or grabbing material over an obstruction.



FRONT-SEATED ARTICULATION. Front-seated articulation helps the machine work in compact jobsites while keeping turf disturbance a priority.



LIFT-CAPACITY-TO-WEIGHT RATIO. The ATX720 has a rated operating capacity of 1,939 lb (880 kg) while having a standard weight of 3,911 lb (1,774 kg). This lift-capacity-to-weight ratio allows contractors to use a light machine while still being able to carry heavy materials on the jobsite.



COMPACT SIZE. With narrow tires, the ATX720 is 44.5-in (113-cm) wide, while the wider tires make the machine 50.4-in (128-cm) wide. The standard tire configuration allows the ATX720 to fit through a standard 4-ft (1-m) gate for backyard access on landscape jobs.



FOUR-WHEEL DRIVE HYDROSTATIC DIRECT DRIVE MOTORS. As each wheel has a hydrostatic direct drive motor, hydraulic oil can flow freely to each wheel as needed during transport which helps reduce ground disturbance on turf when making turns. The four-wheel drive hydrostatic direct drive motors also allow for the use of the DBS and torque divider to increase tractive effort in difficult conditions.



OPERATOR COMFORT. The adjustable seat and operator station layout allows operators to work comfortably for a full day. Options like a heated seat, enclosed and heated cab, and work lights add comfort for year-round use of the ATX720.

ATX720 COMPACT ARTICULATED LOADER

GENERAL DIMENSIONS

Length: 109.8 in (278.9 cm)

Width: 44.5 in (113 cm)

Height: 79.5 in (202 cm)

Weight (with rear weights and no attachments): 3,911 lb (1,774 kg)

Ground clearance: 8.3 in (21 cm)

Angle of departure with rear weights: 19°

ENGINE

Make/model: Kubota D1305 Tier 4 Final

Fuel type: Diesel

Fuel tank capacity: 9 gal (34 L)

Gross horsepower: 25 hp (19 kW)

Cooling system: Liquid

Transmission: Hydrostatic

PERFORMANCE

Rated operating capacity (straight)*: 1,939 lb (880 kg)

Rated operating capacity (articulated)*: 1,492 lb (677 kg)

Travel speed: 5.6 mph (9 km/hr)

Turning radius (inside/outside): 32.5 in - 82.3 in (82.6 cm - 209 cm)

Standard tires: 23x10.50-12

Pivot point height (extended boom): 114 in (290 cm)

Outreach with horizontal boom (extended boom): 46.6 in (118 cm)

*Operating capacities shown have the boom low to the ground, boom not extended and the rear counterweights installed. The rating shown is for a fork attachment at 80% of the tipping load per EN 474-3:2006+A1:2019.

HYDRAULIC SYSTEM

Auxiliary hydraulics oil flow: 9.8 gpm (37 L/min)

Hydraulic oil tank capacity: 11.1 gal (42 L)

NOTES:

MultiOne SRL Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components specific to their global region. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo and Equipped to Do More are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Kubota is a trademark of Kubota Engine Corporation.

© 2023 Vermeer Corporation. All Rights Reserved.



EQUIPPED TO DO MORE.