

# SPX25 DROP PLOW



**REMOTE CONTROL.** A remote control gives you 360-degree control of the machine, providing greater maneuverability on tight jobsites, as well as visibility to the complete worksite and to avoid potential obstacles or obstructions that may be difficult to operate with conventional controls.



**COMPACT SIZE.** A narrow width of 34.5 in (87.6 cm) and length of 81 in (205.7 cm) allows you to enter gated yards and install utilities in tight jobsites.



**DECREASE TURF DISTURBANCE.** Dual rubber tracks with a ground pressure of 3.7 psi (.3 bar) minimize disturbance and restoration to the jobsite while tackling tough ground conditions. This lightweight plow will also help save time with a 3.7 mph (6 km/h) transport speed.



**OPTIONAL REEL CARRIER.** Add an optional reel carrier for increased productivity and efficiency.



**PORTA BORING.** Easily transition from plowing to boring under driveways, sidewalks and other obstacles with an optional Porta Bore attachment.



**INCREASED VISIBILITY.** Allows the operator to have a full, unobstructed view of the machine and product installation.

# SPX25 DROP PLOW

## GENERAL

Length: 81 in (205.7 cm)

Width: 34.5 in (87.6 cm)

Height: 40.5 in (102.9 cm)

Weight: 1600 lb (725.7 kg)

## ENGINE

Make and model: Rehlko Command PRO ECH740

Fuel type: Gas

Gross horsepower: 25 hp (18.6 kW)

Cooling medium: Forced air

## HYDRAULIC SYSTEM

Attachment pump relief pressure (trencher/forward):  
2600 psi (179.4 bar)

Attachment aux relief pressure: 2900 psi (200 bar)

Ground drive pump relief pressure forward/reverse:  
2900 psi (200 bar)

Ground drive pump at maximum engine rpm: 13.3 gpm (50.4 L/min)

Attachment pump at maximum engine rpm: 15.7 gpm (59.4 L/min)

Attachment aux pump: 3.8 gpm (14.4 L/min)

## CAPACITIES

Fuel tank: 6.8 gal (25.7 L)

Hydraulic tank: 8 gal (30.3 L)

Hydraulic system: 8.5 gal (32.2 L)

Engine oil: 0.5 gal (1.9 L)

## GROUND DRIVE (TRACKS)

Track contact length: 31.3 in (79.4 cm)

Track width: 7 in (17.8 cm)

Ground drive type: Hydrostatic

Maximum transport speed: 3.7 mph (6 km/h)

## ATTACHMENT OPTIONS

Plow

Porta bore

Reel carrier/weight kit

## NOTES:

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

