

ATX960

COMPACT ARTICULATED LOADER



TELESCOPIC BOOM. The telescopic boom on the ATX960 extends 31.5 in (80 cm) for loading materials to a dump height of 126 in (320 cm) in hinge pin height. The telescopic boom can also aid in dumping material over the backside of a retaining wall or grabbing material over an obstruction.



COMPACT SIZE. With a narrow tire option, the ATX960 is 52-in (132-cm) wide, while the standard tires make the machine 59-in (149.9-cm) wide. The standard length of the ATX960 is 141 in (358.1 cm).



OPERATOR COMFORT. The adjustable seat and operator station layout allows operators to work comfortably for a full day. Options like a heated seat, enclosed and heated cab, and optional air conditioning add more comfort for year-round use to the ATX960.



MULTIFUNCTION JOYSTICK. The multifunction joystick utilizes electric-over-hydraulic toggles for ease of access to machine functions like the telescopic boom, auxiliary hydraulic controls and the DBS. The operator does not have to remove their hand from the loader arm controls in order to function any of these features.



LIFT-CAPACITY-TO-WEIGHT RATIO. The ATX960 has a rated operating capacity (straight) of 3,285 lb (1,490 kg) while having a standard weight of 6,040 lb (2,740 kg) with rear and side weights and without attachments. This lift-capacity-to-weight ratio allows contractors to use a lighter machine while still being able to carry heavy materials on the jobsite.



FULL-SIZED ATTACHMENT PLATE. The full-sized attachment plate on the ATX960 is compatible with full-sized articulated loader attachments. The ATX960 can be fitted with various authorized attachments to meet the jobsite need, may that be for snow removal, landscaping, logging and tree care work, or various other applications.

ATX960 COMPACT ARTICULATED LOADER

GENERAL

Length (with rear weights): 141 in (358.1 cm)

Width (varies with tire size): 59 in (149.9 cm)

Height (varies with options): 84.6 in (214.9 cm)

Weight (with weights and no attachments): 6,040 lb (2,739.7 kg)

Ground clearance: 13.4 in (34 cm)

Angle of departure with rear weights: 19°

Attachment plate: Full-size attachment plate

ENGINE

Make/Model: Kohler KDI1903 Tier 4 Final

Fuel type: Diesel

Fuel tank capacity: 13.2 gal (50 L)

Gross horsepower: 57 hp (42.5 kW)

Cooling system: Liquid

Transmission: Hydrostatic

PERFORMANCE

Rated operating capacity (straight): 3,285 lb (1,490 kg)

Rated operating capacity (articulated): 2,158 lb (991.1 kg)

Travel speed: 8 mph - 16.7 mph (12.8 km/hr - 26.9 km/hr)

Turning radius (inside/outside): 40.5 in/100.4 in (102.9 cm/255 cm)

Standard tires: 31x15.50-15

Pivot point height (extended boom): 126 in (320 cm)

Outreach of horizontal boom (extended boom): 31.5 in (80 cm)

HYDRAULIC SYSTEM

Auxiliary hydraulics oil flow: 25 gpm (80 L/min)

Hydraulic oil tank capacity: 15.6 gal (59.1 L)

STANDARD FEATURES

Multifunction joystick

HI-Flow System

Dynamic Blocking System (DBS)

Torque divider

Self-leveling double-H telescopic boom

ROPS-FOPS Level I

Two front working lights

Ergonomic full adjustable suspension seat with armrests and seat belt

OPTIONS

A/C system with heating for fully enclosed cab

Additional front hydraulic outlets

Backup warning beeper

Beacon light

Heating system

Mirrors

Rear 12V electric socket

Rear side weights (176 lb or 352 lb) (79.8 kg or 159.7 kg)

Rear weights (396 lb or 970 lb) (179.6 kg or 440 kg)

Skid, turf and tractor tires

LED working lights

ROPS-FOPS Level I

LCD graphic display with programmed service

2 front working lights

Ergonomic adjustable seat with armrests and seat belt

VERMEER STANDARD LIMITED WARRANTY

Material and workmanship: 2 years/1,000 hours

Hydraulic pumps and drive motors: 3 years/1,000 hours

MultiOne, SRL Corporation reserve the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo and Equipped to Do More are all trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Kohler is a trademark of Kohler Co.

© 2025 Vermeer Corporation. All Rights Reserved.

